


DIP32 TO TSOP32 UNIVERSAL SOCKET ADAPTER ACCEPT TSOP32 package (Width = 14mm)



ADA-TSOP32-14


Introduction:

This universal adapter connect the pins of a TSOP32 device (width = 14mm) to a 32 pin DIP equivalent.
It accept a TSOP-14 device and plug into a DIP socket.
Socket type "open".

Connections of this adapter:

DIP32	TSOP32 (standard) (live bug)	TSOP32 (reverse) (dead bug)	TSOP32 (reverse) (dead bug)	TSOP32 (standard) (live bug)	DIP32
1	9	24	25	8	32
2	10	23	26	7	31
3	11	22	27	6	30
4	12	21	28	5	29
5	13	20	29	4	28
6	14	19	30	3	27
7	15	18	31	2	26
8	16	17	32	1	25
9	17	16	1	32	24
10	18	15	2	31	23
11	19	14	3	30	22
12	20	13	4	29	21
13	21	12	5	28	20
14	22	11	6	27	19
15	23	10	7	26	18
16	24	9	8	25	17

Dimensions of the devices accepted:



Package TSOP32-14:



Examples of supported devices:
SST SST39VF010

Equivalent adapters from other manufacturers:
WL-TSOP32-T / WL-TSOP32-U002
PA32TS32-14 / PA32TS14-OT
SA620

Item includes:

Adapter.
User manual in English and French.